

Technical Bulletin

Model

All

Group

0

Subject:

**Approximate Oil/Fluid Capacities
for All Models from 1985**

Part Identifier

N/A

Number

9401

ATTENTION: Service Manager / Service Technician

Models	Engine Oil w/Filter *1&*2 Dry	Engine Oil w/Filter Service Fill *8	Engine Coolant *1&*5	ATF Auto Trans *1,*2&*3 Dry	ATF Service Fill *8	Final Drive Auto Trans *1&*7	Manual Trans *1&*4	Brake Fluid *1&*6	Washer Fluid
944	6.4	6.0	9.0	6.3	3.0	1.1	2.1	0.3	6.3
944S/S2/T	6.8	6.0	9.0	N/A	N/A	N/A	2.1	0.3	6.3
968	7.4	6.5	8.4	7.4	3.0	0.6	2.9	0.3	6.9
928S	8.0	7.5	17.0	6.3	5.0	2.8	4.0	0.3	9.5
928 S4	8.0	7.5	17.0	7.7	6.0	3.0	4.7	0.3	7.9
928 GTS	8.0	7.5	17.0	9.8	8.0	2.0	5.0	0.3	7.9
911	13.0	10.0	N/A	N/A	N/A	N/A	3.2	0.3	8.4
911 Turbo up to 1989	13.0	10.0	N/A	N/A	N/A	N/A	3.9	0.3	8.4
911 C2	12.0	10.0	N/A	9.0	3.0	1.0	3.8	0.4	7.8
911 C4	12.0	10.0	N/A	N/A	N/A	N/A	4.0	0.8	7.8
911 Turbo from 1991	13.0	10.0	N/A	N/A	N/A	N/A	3.9	0.8	7.8
993	12.0	10.0	N/A	9.5	3.0	0.9	3.8	0.4	7.7

NOTE: ALL CAPACITIES ARE GIVEN IN QUARTS

- *1. Filling capacities are approximations; actual fill will usually be less.
- *2. Dry capacity is the capacity after complete disassembly of an entire system including coolers and lines.
- *3. Automatic transmission fluid is Dexron IID.
- *4. Manual transmission oil is multigrade gear oil 75W90 with API classification GL5.
- *5. Antifreeze must be phosphate free.
- *6. From model year 1993 use only DOT 4 brake fluid. (Porsche Part Number 000 043 202 09)
- *7. Up to model year 1988 use SAE 90W with API classification GL5; from model year 1989 use multigrade gear oil 75W90 with API classification GL5.
- *8. Service fill is the amount of oil required when performing normal maintenance.

IMPORTANT-After initial filling, adhere to the manufacturer's instructions for checking and correcting oil/fluid levels with regard to engine temperature. Top up oil/fluid levels as required.



PORSCHE CARS NORTH AMERICA INC.