

Mobilube SHC 75W-90, 80W-140

Supreme Performance Commercial Gear Lubricants

Product Description

DISCONTINUED - The recommended replacement product is Mobil Delvac Synthetic Gear Oil 75W-90, 80W-140.

Mobilube SHC 75W-90 and 80W-140 are synthetic drivetrain lubricants engineered to meet the most demanding extended drain and warranty requirements. These products are designed for use in heavy-duty drivetrains that require gear lubricants with relatively high viscosity and excellent load-carrying capability and where extreme pressures and shock loading are expected. Mobilube SHC 75W-90 and 80W-140 incorporates the latest technology in synthetic basestocks and advanced additives providing significant advantages over mineral gear oils.

The state-of-the-art technology in Mobilube SHC 75W-90 and 80W-140 delivers unsurpassed performance for low and high temperature application, protection against thermal degradation and oxidation, reduced wear and corrosion, improved shear stability, extended service capability, and excellent fuel economy. These products meet API service MT-1/GL-5 EP gear oil service classification and perform at the MIL-PRF-2105E level.

The outstanding performance of this product is confirmed by its approval for final drives covered by Eaton Roadranger (E500) and ArvinMeritor Extended Warranties of 750,000 miles, with extended oil drains of 500,000 miles. They are also approved by Mack against GO-J Plus (75W-90) and GO-J (80W-140) extended service classifications.

Features & Benefits

Today's technology has vastly improved the performance capabilities of heavy-duty on and off-highway equipment load, torque, speed, and control through innovative drivetrain designs. These designs have changed and increased the requirements of lubricants to deliver this higher level of performance, increase productivity, and reduce operating costs. For heavy-duty final drives, friction control, wear protection, thermal stability, shear stability, rust and corrosion prevention, and seal protection are features that must be optimally balanced to provide extended gear and seal life, smooth operation, improved fuel economy and high load high torque capability over a wide range of applications. The key benefits of Mobilube SHC 75W-90 and 80W-140 include:

| Features | Advantages and Potential Benefits |
|--|--|
| Exceptional thermal stability and resistance to high temperature oxidation | Extended gear and bearing life due to minimal deposits Longer seal life |
| Outstanding protection against low speed/high torque wear and high speed scoring | Increased load-carrying capability. Reduced maintenance costs and longer equipment life |
| Exceptional shear stability | Retains viscosity and film strength under severe operating conditions to prevent wear |
| Excellent rust, staining, and corrosion protection of copper and | Reduced wear and longer component life |

ExxonMobil Lubricants & Specialties

All products may not be available locally. For more information, contact your local sales office or visit www.exxonmobil.com.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

© 2001 Exxon Mobil Corporation. All rights reserved.



| Features | Advantages and Potential Benefits |
|--|---|
| its alloys | |
| Enhanced friction reduction properties | Improved fuel economy and reduced operating costs |
| Outstanding low temperature fluidity versus mineral oils | Reduced wear and ease of start-up |
| Good resistance to foaming | Maintains film strength for reliable lubrication |
| Compatible with typical automotive seals and gaskets | Minimum leakage and reduced contamination |

Applications

- Heavy-duty manual transmissions, axles and final drives requiring API GL-5 & MT-1 performance
- On-highway light and heavy-duty trucks, busses and vans
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Other heavy-duty industrial gear drives including hypoid and worm gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque conditions prevail
- Mobilube SHC 75W-90 and 80W-140 are intended for initial fill, topping-off or refilling differentials, final drives, transfer cases and other gear applications where lubricants meeting MIL-PRF-2105E, API Service GL-5 , EP gear lubricants are recommended
- Recommended for equipment such as winch reduction gears and crawler vehicle propulsion gear drives that are exposed to severe low temperatures
- Use as a companion with Mobiltrans SHC 50 in transmissions for maximum drive train life, efficiency and fuel economy improvement
- Recommended where extended service intervals and warranties are required
- Not recommended for applications requiring API GL-4 Level performance
- Not intended for automatic, manual or semiautomatic transmissions for which engine oil or automatic transmission fluids are recommended

Specifications & Approvals

| Mobilube SHC Gear Oil meets the following industry and builder specifications: | 75W-90 | 80W-140 |
|--|--------|---------|
| API GL-5/MT-1 | X | X |
| Dana Shaes 256 | X | X |

| Mobilube SHC Gear Oil has the following builder approvals: | 75W-90 | 80W-140 |
|--|--------|---------|
| Eaton E500 PS 163/037 | X | X |
| Mack GO-J Plus | X | |
| Mack GO-J | | X |
| ArvinMeritor 0-76N | X | X |

| Mobilube SHC Gear Oil has the following military approval: | 75W-90 | 80W-140 |
|--|--------|---------|
| MIL-PRF 2105E quality level | X | X |



Typical Properties

| Mobilube SHC | 75W-90 | 80W-140 |
|----------------------------------|---------------|----------------|
| SAE Grade | 75W-90 | 80W-140 |
| Viscosity, ASTM D 445 | | |
| cSt @ 40°C | 120 | 310 |
| cSt @ 100°C | 15.9 | 31.2 |
| Viscosity Index, ASTM D 2270 | 140 | 139 |
| Pour Point, °C, ASTM D 97 | -48 | -36 |
| Flash Point, °C, ASTM D 92 | 205 | 210 |
| Density @ 15°C kg/l, ASTM D 4052 | 0.859 | 0.870 |

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, Mobilube and SHC are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

