

PHONE DIAL™ fitment guide

Model Series	Type	Application	18 X 8 ET57	18 X 9 ET69	18 X 9 ET57	18 X 9.5 ET76	18 X 9.5 ET50	18 X 10.5 ET63
928	All (77-95)	Front		✓ a				
928	Early and S (77-83)	Rear				✓ e	✓	✓ d
928	Mid-Year S (84-86)	Rear				✓ b	✓ c	✓ c d
928	S4/GT (87-91)	Rear				✓ e	✓	✓ d
928	GTS (92-95)	Rear				✓ e	✓ e	✓ f
944, 951	Early Offset (82-86)	Front	✓ e	✓ e				
944, 951	Early Offset (82-86)	Rear			✓ e		✓ e	
944, 951, 968	Late Offset (87-96)	Front	✓	✓				
944, 951, 968	Late Offset (87-96)	Rear			✓		✓	

 Recommended
  Alternate

a - 245 tire recom'd, 255 max / b - use w/OE 17mm or 21mm spacer / c - no spacer, open lug nuts req'd
 d - may req' rolling and/or spacer / e - custom spacer req'd / f - use w/OE 38mm spacer



www.928ClassicS.com

THIS DRAWING AND INFORMATION CONTAINED IN THIS DRAWING ARE PROPERTY OF 928 CLASSICS LLC. NO PART OF THIS DRAWING OR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR TRANSFERRED WITHOUT THE WRITTEN PERMISSION OF 928 CLASSICS LLC.

jim@928classics.com